# IPv6 Deployment Planning

### **ISP** Workshops



These materials are licensed under the Creative Commons Attribution-NonCommercial 4.0 International license (http://creativecommons.org/licenses/by-nc/4.0/)

Last updated 1<sup>st</sup> November 2016

# Acknowledgements

- This material originated from the Cisco ISP/IXP Workshop Programme developed by Philip Smith & Barry Greene
- Use of these materials is encouraged as long as the source is fully acknowledged and this notice remains in place
- Bug fixes and improvements are welcomed
  - Please email workshop (at) bgp4all.com

Philip Smith

### Introduction

- Presentation introduces the high level planning considerations which any network operator needs to be aware of prior to deploying IPv6
- Content applicable for:
  - Business decision makers
  - Network managers
  - Network engineers
    - Will also require implementation detail

# Agenda

- 1. Goals
- 2. Network Assessment
- 3. Network Optimisation
- 4. Procuring IPv6 Address Space
- 5. IPv6 Address plan
- 6. Deployment
- 7. Seeking IPv6 Transit
- 8. Customers

# Goals

#### What do we want to achieve?

## Goals

# Ultimate aim is to provide IPv6 to our customers:

- Customers = end users
- Customers = content providers

Strategy depends on network transport:

- Native IP backbone
  - Dual Stack is the solution
- MPLS backbone (tunnels)
  - 6PE or 6VPE is the solution
  - The core infrastructure will remain IPv4 only

### Native IP Backbone

#### Routers are the infrastructure


- Customer connections connect to the native backbone
- VPN services provided using GRE, IPSEC, IPinIP etc
- Providing IPv6 for customers means upgrading the native infrastructure to dual-stack



### MPLS Backbone

#### Routers are the infrastructure

- Public and Private network access provided within the MPLS cloud
- The core network does NOT need to be IPv6 aware
- IPv6 access provided by 6PE or 6VPE
- Provider Edge routers need dual stack capability



# Network Assessment

# What can run IPv6 today, and what needs to be upgraded?

# Audit

#### ■ First step in any deployment:

- Review existing network infrastructure
- Primarily routers across backbone
  - Perhaps also critical servers and services (but not essential as initial focus is on routing infrastructure)

### Process

#### Analyse each location/PoP

#### Document

- Router or any other L3 device
- RAM (installed and used)
- Non-Volatile Configuration memory
- Software release versions
- Most network operators already keep track of this info
  If not, RANCID (www.shrubbery.net/rancid/) makes this very easy

#### Sanity check

- Check existing connectivity
- Remove unused configuration
- Shutdown and clean up unused interfaces

# Software Issues (1)

- Does the existing software have IPv6 support?
  - Yes: deployment is straightforward
  - No: investigate cost of upgrade
- Is a software upgrade available?
  - Yes: is hardware suitably specified?
  - No: hardware replacement
- Implement software upgrade
  - Budget, purchase & schedule installation

# Software Issues (2)

#### □ If existing software supports IPv6:

- Are deployed software versions consistent across infrastructure?
  - Recommend maximum of two variations (easier troubleshooting, bug tolerance, etc)

#### □ If existing software does not support IPv6:

- Cost of upgrade to a version which does?
- Testing for existing feature compatibility:
  - A software image with IPv6 may have "lost" features required for the existing operational network

### Hardware Issues

Can hardware specification be upgraded (eg RAM, NVRAM, etc)?

- Yes: budget, purchase, installation
- No: hardware replacement

□ Hardware replacement:

- Assess suitable replacement product
- Analyse impact on operating network, existing services and customer

## Result

- Once the previous steps are completed, entire network is running IPv6 capable software
- Deployment of IPv6 can now begin

# Network Optimisation

# Is the IPv4 network the best it can be?

# Optimisation

- IPv4 networks have been deployed and operational for many years
  - Your network may fall into this category
- Optimisation means:
  - Does the interior routing protocol make sense?
  - Do all routing protocols have the latest best practices implemented?
  - Are the IGP metrics set so that primary and backup paths operate as expected?

## Motivation for Optimisation

- IPv6 deployment (apart from MPLS cores) will be dual stack
  - Which means sitting alongside existing IPv4 configurations
- Aim is to avoid replicating IPv4 "shortcuts" or "mistakes" when deploying IPv6
  - IPv6 configuration will replicate existing IPv4 configuration
- Improvements in routing protocol BCPs should be deployed and tested for IPv4
  - Take the opportunity to "modernise" the network

# Procuring IPv6 address space

Now we need addresses...

# Getting IPv6 address space (1)

#### From your Regional Internet Registry

- Become a member of your Regional Internet Registry and get your own allocation
  - Membership usually open to all network operators
  - RIR specific details for IPv6 allocations are listed on the individual RIR website
- Open to all organisations who are operating a network
- Receive a /32 (or larger if you will have more than 65k /48 assignments)

# Getting IPv6 address space (2)

#### From your upstream ISP

- Receive a /48 from upstream ISP's IPv6 address block
- Receive more than one /48 if you have more than 65k subnets

#### □ If you need to multihome:

- Apply for a /48 assignment from your RIR
- Trying to multihome with provider's /48 will be operationally challenging

Provider policies, filters, etc

# Address Planning

IPv6 address space available to each network operator is large compared with IPv4

- Design a scalable plan
- Be aware of industry current practices
- Separation of infrastructure and customer addressing
- Distribution of address space according to function

# Addressing Plans – Infrastructure

- Network Operators should procure a /32 from their RIR
- Address block for infrastructure
  - /48 allows 65k subnets in the backbone
- Address block for router loop-back interfaces
  - Number all loopbacks out of one infrastructure /64
  - /128 per loopback
- Point-to-point links
  - /64 reserved for each, address as a /127
- LANs
  - /64 for each LAN

## Addressing Plans – Customer

#### Customers get one /48

- Unless they have more than 65k subnets in which case they get a second /48 (and so on)
- Industry standard for customer assignments today:
  - /64 for just one LAN
  - /56 for a small network
  - /48 for a large network

# Deploying IPv6

#### Now we put it onto the network

# IPv6 Deployment

- Number all the infrastructure interfaces according to the established addressing plan
  - No customers yet
- Secure routers and L3 devices for IPv6 access
- Enable IPv6 internal routing protocols
  - First IGP care needed not to break IPv4 connectivity
  - iBGP should replicate IPv4 iBGP
- Check that operation compares with IPv4 operation
  - Fix any problems in a dual stack network the protocols must function the same way

# Seeking IPv6 Transit

# Hello World, I'd like to talk to you...

# Seeking Transit

- Most transit ISPs now offer native IPv6 transit
- Next step is to decide:
  - To give transit business to those who will accept a dual stack connection

#### or

To stay with existing IPv4 provider and seek a tunnelled IPv6 transit from an IPv6 provider

### Dual Stack Transit Provider

#### Fall into two categories:

- A. Those who sell you a pipe over which you send packets
- B. Those who sell you an IPv4 connection and charge extra to carry IPv6
- ISPs in category A are much preferred to those in category B
- Charging extra for native IPv6 is absurd, given that this can be easily bypassed by tunnelling IPv6
  - IPv6 is simply protocol 41 in the range of IP protocol numbers

### Dual Stack Transit Provider

#### Advantages:

- Can align BGP policies for IPv4 and IPv6 perhaps making them more manageable
- Saves money they charge you for bits on the wire, not their colour

#### Disadvantages:

Not aware of any

## Separate IPv4 and IPv6 transit

- Retain transit from resolute IPv4-only provider
  - You pay for your pipe at whatever \$ per Mbps
- Buy transit from an IPv6 provider
  - You pay for your pipe at whatever \$ per Mbps
- Luck may uncover an IPv6 provider who provides transit for free
  - Getting more and more rare as more ISPs adopt IPv6

## Separate IPv4 and IPv6 transit

#### Advantages:

- Not aware of any
- But perhaps situation is unavoidable as long as main IPv4 transit provider can't provide IPv6
- And could be a tool to leverage IPv4 transit provider to deploy IPv6 – or lose business

#### Disadvantages:

- Do the \$\$ numbers add up for this option?
- Separate policies for IPv4 and IPv6 more to manage

# Customer Connections

Network is done, now let's connect paying customers...

### Customer Connections

- Giving connectivity to customers is the biggest challenge facing all ISPs
- Needs special care and attention, even updating of infrastructure and equipment
  - Cable/ADSL
  - Dial
  - Leased lines
  - Wireless Broadband

## IPv6 to Broadband Customers

Method 1: Use existing technology and CPE

- This is the simplest option it looks and feels like existing IPv4 service
- PPPoE + DHCPv6 PD
- Used by ISPs such as Internode (AU) and XS4ALL (NL)
- Issues:
  - IPv6 CPE are generally more expensive (not the "throwaway" consumer devices yet)
  - Cheaper CPE have no IPv6 yet need to be replaced/ upgraded

## IPv6 to Broadband Customers

□ Method 2: use 6rd

- This is for when Broadband infrastructure cannot be upgraded to support IPv6
- Used by ISPs such as FREE (FR)
- Example:
  - **2001**:db8:6000::/48 assigned to 6rd
  - Customer gets 192.168.4.5/32 by DHCP for IPv4 link
  - IPv6 addr is 2001:db8:6000:0405::/64 for their LAN (taking last 16 bits of IPv4 address)
  - DHCPv6 PD can be used here too (eg to give /56s to customers)

Issues:

All CPE needs to be replaced/upgraded to support 6rd

# IPv6 to Dialup Customers

Use existing technology:

- Most dialup access routers are easily upgradable to support IPv6
- Service looks and feels like the IPv4 service
- PPPv6 (with DHCPv6 PD perhaps)
- CPE is usually PC or laptop (and most OSes have supported IPv6 for many years)
- Service already offered for several years by many ISPs

### IPv6 to Fixed Link Customers

Use existing technology:

- Most access routers (PE) and Customer routers (CPE) are easily upgradeable or replaceable to include IPv6 support
- Service looks and feels like existing IPv4 service
- Configuration options:
  - IPv6 unnumbered on point to point links (or address them)
  - Static routes, subnet size according to business size
  - Or use BGP with private or public (multihomed) ASN
  - Whatever is done for IPv4 should be repeated for IPv6
- Fixed link Customers are probably the easiest to roll IPv6 out to
  - Customer deploying IPv6 within their own networks is a separate discussion (rerun of this presentation!)

## IPv6 to Customers

- What about addressing? Here is a typical strategy:
  - Mobile Device:
    - □ /64 = 1 subnet
  - Home/Small Organisation:
    - /56 = 256 subnets
    - **Reserve the whole /48**
  - Enterprise/Large Organisation:
    - /48 = 65536 subnets

### Customer Connections

What about customer end systems?

- Is IPv6 available on all their computers and other network connected devices?
- How to migrate those which aren't?
- How to educate customer operations staff
- What about their CPE?
- What about the link between your edge device and their CPE?
- What about security?

# Conclusion

We are done...!

# Conclusion

- When deploying IPv6 for the first time, a strategy and planning are of paramount importance
- Presentation has highlighted the steps in the planning and deployment process
  - Variations on the theme are quite likely there is no single correct way of proceeding

IPv6 Deployment Planning

**ISP** Workshops